



**3.1 ΠΙΝΑΚΑΣ ΕΞΑΡΤΗΜΑΤΩΝ ΣΤΗΛΗΣ ΑΝΑΙΣΘΗΣΙΟΛΟΓΟΥ**

A/A	ΦΩΤΟΓΡΑΦΙΑ	ΠΕΡΙΓΡΑΦΗ ΜΑQUET	ΚΩΔΙΚΟΣ	ΠΟΣΟ ΤΗΤΑ (ΤΜΧ)
1		Type Heavy for M-Lifting – 2 beams of 900 mm + 900 mm – gross load capacity: 345 Kg / 761 lbs – 3 articulations (ceiling brackets included), with beam plus reserved.	SU0002990016	1
2		Modular ceiling attachment < 23,6 inches / 60 cm (with M16 threaded rods on 270 mm) for ceiling pendants all ranges .	SU0004990012	1
3	N/A	Electrical isolating kit (16 pieces) for installations of ceiling pendants.	ARD517003948	1
4	N/A	Kit of 6 plugs HSLB Hilti for anchorage plates AN1003, ANE 1004, ANPB 1004, ANPB 1004 and for ceiling attachment systems of modutec , AlphaPort , and M-Lifting .	ARD514251999	1
5		Gas kit for modutec (3 holes- maximum 6 gas circuits) – to be fixed on the intermediate plate.	ARD517003712	1
6		Standard plate connecting the beam to the ceiling attachment or the anchorage plate for Modutec HH and motorized pendants (M PWR 6-8, 9-8 and 12-8 series).	ARD517005951	1
7		Single Semi-curved ceiling cover (two parts, height = 105 mm) for Modutec and for satellite range when mounted with ceiling attachment.	ARD517068999	1
8	N/A	Suspension tube 500 mm with rigid cover strip R1 (W=80 mm / 3.2 inches) .	SU0006000000	1
9		Distribution module “Console “ 600 mm / 23,6 inches with 6 panels – 2 on the front , 2 on sides , and 2 on the back (16 flexible conduits) and one cover strip R1 (W=80mm / 3,2 inches) on the front – Load capacity : 200 kg /441 Lbs , only for M-Lifting .	SU0006990000	1

10		Shelf (W X D= 400 x 500 mm / 15,7 X 19,7 inches) with Grey corners, handle (400mm / 15,7 inches), 2 rails of 450mm / 17,7 inches and bottom cover – loading capacity: 80 kgr / 176 lbs (limited to 50 kg / 110 lbs with cabinet drawers).	SU0005000012	1
11		Single arm for flat screen (length 400mm) with swivel and tilt including VESA 75 X 100 adapter: Load capacity 8 kgr / 17,6 lbs.	ARD513950999	1
12		25mm / 1 inch spacer in order to shift a Modutec shelf or a drawer cabinet (400 , 500 , and 600 mm / 15,7 , 19,7 , 23,6 inches) from the distribution module ; to be mounted on R1 strips.	ARD517052900	1
13	N/A	Motor driven column of 400 mm / 16 inches vertical movement – 230 V – using with “Console” for M-Lifting is compulsory.	SU 0006020015	1
14		Electrical outlet 10/16A + earth connected, standby, mosaic 45, French model.	ARD517001922	6
15		Electrical outlet 10/16A + earth connected, standby, mosaic 45, French model.	ARD517001923	6
16		Equipotential outlet with line.	ARD517001916	12
17		Compressed Air 3 bar outlet Als model.	ARD517001891	3
18		Oxygen O2 outlet – Als model.	ARD517001893	3

19		Nitrous Oxide (N <sub>2</sub> O) outlet – Als model.	ARD517001892	2
20		Vacuum outlet – Als model.	ARD517001889	3
21	N/A	Anesthesia gas evacuation outlet including operating indicator – biolume brand.	ARD517001867	1
22		Double connector network cat 6E Female socket, equipped with a male shielded RJ45 plug cable – length 5 m.	ARD517099991	2
23		Cables winding wheel on metal plate (mounted on R1 strip).	ARD517003954	1
24	N/A	Docking system (Draeger standard) for Draeger / Datex Ohmeda anaesthesia machine, MIS trolley.	SU0005990003	1
25		Control unit for electropneumatic brake system on 2 or 3 axes – haw to be integrated on the handles of shelves.	ARD517003222	1
26		Pressure regulator for brake system.	SU0002990028	1
27	N/A	Electropneumatic brake system for 2 Axes of Modutec medium, Medium- Heavy, Heavy and motorized series.	SU0002990085	1
28		Power supply for ambient light bands and electropneumatic brakes – 100, 110V and 220V compatible.	ARD517003973	1
29		Adaptor for strips R2 to R1.	ARD517003998	2

30		<p>1 short articulation with 1 IV stand tube (25mm, 1100 mm/ 39,4 inches , 4 hooks in a straight line, loading capacity 20 kg / 44 lbs) for strip R1.Has to be fixed either directly on strip R1 of the Modutec distribution tubes (tub dis XXX) , or on the adaptor for strips R2-R1.</p>	ARD517003975	1
31		<p>Adaptor for strips R2 to R1.</p>	ARD517003998	1